

*SUPPLIERS OF AIR CONDITIONING—PLUMBING & HEATING—MECHANICAL PRODUCTS—
VENTILATION EQUIPMENT*

SUBJECT.....GLASSFLEX FLEXIBLE DUCTING(TFG).

APPLICATION

TRADE SUPPLIES 'TFG' IS A RANGE OF FULLY FLEXIBLE REINFORCED DUCTING, WHICH HAS BEEN MANUFACTURED FOR THE HVAC MARKET & INDUSTRIAL PURPOSES. IT IS SUITABLE FOR ALL NORMAL VENTILATION AND AIR CONDITIONING SYSTEMS, INCLUDING HIGH PRESSURE, AND SUCCESSFULLY WITHSTANDS CONSTANT BENDING OR FLEXING.



CONSTRUCTION

TRADE SUPPLIES 'TFG' IS A FULLY FLEXIBLE POLYESTER REINFORCED PVC COATED DUCTING WITH AN ENCAPSULATED HIGH TENSILE STEEL WIRE HELIX.

ADVANTAGES

- * SUPPLIED IN STANDARD 6 METER LENGTH, COMPRESSED TO 0.8 MTS.
- * INDIVIDUALLY BOXED.
- * EASY TO CONNECT TO EITHER ROUND OR OVAL DUCTING.
- * NO SPECIAL TOOLS REQUIRED FOR CUTTING OR FIXING.

TECHNICAL DATA

CONSTRUCTION MATERIAL.....REINFORCED POLYESTER PVC
DIAMETER RANGE.....80-610MM
TEMPERATURE RANGE.....-10/+75°C
MAXIMUM AIR VELOCITY.....30 M/SEC
POSITIVE WORKING PRESSURE..3000 PA (MAX)
STANDARD LENGTH.....6 METERS
PACKING.....INDIVIDUAL BOX OF 0.8 METERS
CLAMPING.....LIGHTENING BAND, STAINLESS STEEL
FLEX CLIPS.